User's Guide

M3702C

Make sure to read the **Safety Precautions** before using the product.

Keep the User's Guide(CD) in an accessible place for future reference.

See the label attached on the product and give the information to your dealer when you ask for service.

LG

Safety Precautions

TO REDUCE THE RISK OF ELECTRIC SHOCK DO NOT REMOVE COVER (OR BACK). NO USER SERVICEABLE PARTS INSIDE. REFER TO QUALIFIED SERVICE PERSONNEL.

The lightning flash with arrowhead symbol, within an equilateral triangle, is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.

The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

WARNING/CAUTION

TO REDUCE THE RISK OF FIRE AND ELECTRIC SHOCK, DO NOT EXPOSE THIS PRODUCT TO RAIN OR MOISTURE.

Maintenance and Servicing

Never remove the back cover of the TV : this can expose you to high voltage and other hazards. If the TV does not operate properly, unplug it and call authorized service center or PDI.

Cleaning and Disinfection

Clean the exterior of this TV by removing dust with a lint-free cloth.
Caution : To avoid damage to the surface of the TV, do not use abrasive or chemical cleaning agents.
Clean only with dry cloth.

Note to cable/TV Installer

This reminder is provided to call the CATV system installer's attention to Article 820-40 of the National Electric Code.(U.S.A). The code provides guidelines for proper grounding and, in particular, specifies that the cable ground shall be connected to the grounding system of the building, as close to the point of the cable entry as practical.

WARNING / CAUTION

To prevent fire or shock hazards, do not expose this product to rain or moisture.

FCC NOTICE

Class B digital device

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

CAUTION

Do not attempt to modify this product in any way without written authorization from LG Electronics. Unauthorized modification could void the user's authority to operate this product

Safety Precautions

IMPORTANT SAFETY INSTRUCTIONS

Important safety instructions shall be provided with each apparatus. This information shall be given in a separate booklet or sheet, or be located before any operating instructions in an instruction for installation for use and supplied with the apparatus.

This information shall be given in a language acceptable to the country where the apparatus is intended to be used.

The important safety instructions shall be entitled "Important Safety Instructions". The following safety instructions shall be included where applicable, and, when used, shall be verbatim as follows. Additional safety information may be included by adding statements after the end of the following safety instruction list. At the manufacturer's option, a picture or drawing that illustrates the intent of a specific safety instruction may be placed immediately adjacent to that safety instruction :

Read these instructions.
Keep these instructions.
Heed all warnings.
Follow all instructions.

1. Do not use this apparatus near water

2. Clean only with dry cloth.

3. Do not block any ventilation openings. Install in accordance with the manufacturer's instructions

4. Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.

5. Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong, The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.

6. Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.

7. Only use attachments/accessories specified by the manufacturer.

Safety Precautions

8 Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.

9 Unplug this apparatus during lightning storms or when unused for long periods of time.



10 Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has exposed to rain or moisture, does not operate normally, or has been dropped.

11 Never touch this apparatus or antenna during a thunder or lighting storm.

12 Do not allow a impact shock or any objects to fall into the product, and do not drop onto the screen with something.

13 CAUTION concerning the Power Cord :
Most appliances recommend they be placed upon a dedicated circuit; that is, a single outlet circuit which powers only that appliance and has no additional outlets or branch circuits. Check the specification page of this owner's manual to be certain.

Do not overload wall outlets. Overloaded wall outlets, loose or damaged wall outlets, extension cords, frayed power cords, or damaged or cracked wire insulation are dangerous. Any of these conditions could result in electric shock or fire. Periodically examine the cord of your appliance, and if its appearance indicates damage or deterioration, unplug it, discontinue use of the appliance, and have the cord replaced with an exact replacement part by an authorized servicer. Protect the power cord from physical or mechanical abuse, such as being twisted, kinked, pinched, closed in a door, or walked upon. Pay particular attention to plugs, wall outlets, and the point where the cord exits the appliance.

14 Outdoor Use Marking :
WARNING - To Reduce The Risk Of Fire Or Electric Shock, Do Not Expose This Appliance To Rain Or Moisture

15 Wet Location Marking : Apparatus shall not be exposed to dripping or splashing and no objects filled with liquids, such as vases, shall be placed on or over apparatus.

16 **GROUNDING**

Ensure that you connect the earth ground wire to prevent possible electric shock. If grounding methods are not possible, have a qualified electrician install a separate circuit breaker.

Do not try to ground the unit by connecting it to telephone wires, lightening rods, or gas pipes.



17 **DISCONNECTING DEVICE FROM MAINS**

Mains plug is the disconnecting device. The plug must remain readily operable.

Safety Precautions

Please read these safety precautions carefully before using the product.

⚠ Warning If you ignore the warning message, you may be seriously injured or there is a possibility of accident or death.

⚠ Caution If you ignore the caution message, you may be slightly injured or the product may be damaged

Precautions in installing the Product

⚠ Warning

■ **Keep away from heat sources like electrical heaters.**
- Electrical shock, fire, malfunction or deformation may occur.

■ **Keep the packing anti-moisture material or vinyl packing out of the reach of children.**
- Anti-moisture material is harmful if swallowed. If swallowed by mistake, force the patient to vomit and visit the nearest hospital. Additionally, vinyl packing can cause suffocation. Keep it out of the reach of children.

■ **Do not put heavy objects on the product or sit upon it.**
- If the product collapses or is dropped, you may be injured. Children must pay particular attention.

■ **Do not leave the power or signal cable unattended on the pathway.**
- The passerby can falter, which can cause electrical shock, fire, product breakdown or injury.

■ **Install the product in a neat and dry place.**
- Dust or moisture can cause electrical shock, fire or product damage.

■ **If you can smell smoke or other odors or hear a strange sound unplug the power cord and contact the service center.**
- If you continue to use without taking proper measures, electrical shock or fire can occur.

■ **If you dropped the product or the case is broken, turn off the product and unplug the power cord.**
- If you continue to use without taking proper measures, electrical shock or fire can occur. Contact the service center.

■ **Do not drop an object on or apply impact to the product. Do not throw any toys or objects on the product screen.**
- It can cause injury to human, problem to product and damage the display.

■ **Do not let the product fall or drop when connecting it with an external device.**
- This may cause injury and/or damage to the product.

■ **When connecting it with a game device, keep a distance of four times as long as the diagonal measurement of the screen from the device.**
- If the product falls because of the short cable, this may cause injury and/or damage to the product.

■ **Leaving a fixed image on the screen for a long time may cause damage to the screen and cause image burn-in. Make sure to use a screen saver on the product.**
Burn-in and related problems are not covered by the warranty on this product.

⚠ Caution

■ **Make sure the product ventilation hole is not blocked. Install the product in a suitably wide place (more than 10cm from the wall)**
- If you install the product too close to the wall, it may be deformed or fire can break out due to internal heat.

■ **Do not block the ventilation hole of the product by a tablecloth or curtain.**
- The product can be deformed or fire can break out due to overheating inside the product.

■ **Install the product on a flat and stable place that has no risk of dropping the product.**
- If the product is dropped, you may be injured or the product may be broken.

■ **Install the product where no EMI occurs.**

■ **Keep the product away from direct sunlight.**
- The product can be damaged.

Safety Precautions

Electrical Power Related Precautions

⚠ Warning

■ **Make sure to connect the power cable to the grounded current.**
- You may be electrocuted or injured.

■ **Use the rated voltage only.**
- The product can be damaged, or you may be electrocuted.

■ **In the presence of thunder and lightning, never touch the power cord and signal cable because it can be very dangerous.**
- It can cause electric shock.

■ **Do not connect several extension cords, electrical appliances or electrical heaters to a single outlet. Use a power bar with a grounding terminal designed for exclusive use with the computer.**
- A fire can break out due to overheating.

■ **Do not touch the power plug with wet hands. Additionally, if the cord pin is wet or covered with dust, dry the power plug completely or wipe dust off.**
- You may be electrocuted due to excess moisture.

■ **If you don't intend to use the product for a long time, unplug the power cable from the product.**
- Covering dust can cause a fire, or insulation deterioration can cause electric leakage, electric shock or fire.

■ **Fix the power cable completely.**
- If the power cable is not fixed completely, a fire can break out.

■ **Hold the plug when pulling out the power cable. Do not bend the power cord with excessive force or put heavy objects on the power cord.**
- The power line can be damaged, which may cause electric shock or fire.

■ **Do not insert a conductor (like a metal chopstick) into one end of the power cable while the other end is connected to the input terminal on the wall. Additionally, do not touch the power cable right after plugging into the wall input terminal.**
- You may be electrocuted.

■ **The power supply cord is used as the main disconnection device. Ensure that the socket-outlet is easily accessible after installation.**

■ **Main power breaker is the power cord and this breaking device must be located at a location where it is easy to operate.**

⚠ Caution

■ **Do not unplug the power cord while the product is in use.**
- Electrical shock can damage the product.

Precautions in Moving the Product

⚠ Warning

■ **Make sure to turn off the product.**
- You may be electrocuted or the product can be damaged.

■ **Make sure to remove all cables before moving the product.**
- You may be electrocuted or the product can be damaged.

Safety Precautions

⚠ Caution

■ **Do not shock the product when moving it.**
- You may be electrocuted or the product can be damaged.

■ **Do not dispose the product-packing box. Use it when you move.**

■ **Make the panel face forward and hold it with both hands to move.**
- If you drop the product, the damaged product can cause electric shock or fire. Contact with the service center for repair.

Precautions in Using the Product

⚠ Warning

■ **Do not disassemble, repair or modify the product at your own discretion.**
- Fire or electric shock accident can occur.
- Contact the service center for check, calibration or repair.

■ **When the display is to be left unattended for an extended period of time, unplug it from the wall outlet.**

■ **Keep the product away from water.**
- Fire or electric shock accident can occur.

⚠ Caution

■ **Do not put or store inflammable substances near the product.**
- There is a danger of explosion or fire due to careless handling of the inflammable substances.

■ **When cleaning the brown tube surface, unplug the power cord and scrub with soft cloth to prevent scratching. Do not clean with a wet cloth.**
- The water can sink into the product, which can cause electric shock or serious malfunction.

■ **Take a rest from time to time to protect your vision.**

■ **Keep the product clean at all times.**

■ **Take a comfortable and natural position when working with a product to relax the muscles.**

■ **Take a regular break when working with a product for a long time.**

■ **Do not press strongly upon the panel with a hand or sharp object such as nail, pencil or pen, or make a scratch on it.**

■ **Keep the proper distance from the product.**
- Your vision may be impaired if you look at the product too closely.

■ **Set the appropriate resolution and clock by referring to the User's Guide.**
- Your vision can be impaired.

■ **Use authorized detergent only when cleaning the product. (Do not use benzene, thinner or alcohol.)**
- Product can be deformed.

On Disposal

■ **The fluorescent lamp used in this product contains a small amount of mercury.**

■ **Do not dispose of this product with general household waste.**
Disposal of this product must be carried out in accordance to the regulations of your local authority.

Connecting the Speakers

- Only on some models.

Mount the product onto the speaker by using a screw as shown in the following connect the speaker cable.



After installing your speakers, use holders and cable ties to organize the speaker cables.


Cable holder
Remove the paper.
* This feature is not available in all model.
Cable tie
* This feature is not available in all model.

When the speaker is installed.

*Connect the input terminal with a proper color match.

Using the Remote Control

Name of the Remote Control Buttons



• AV Button

• Sleep Button
When watching **AV, RGB PC,HDMI/DVI ,Component1, Component2**
The product will be automatically turned off after a certain period of time.
Press this button repetitively to select an appropriate time duration

• PSM Button
- Toggles through preset video settings.

There is not a function which is supported

• Menu Button

• UP and Down buttons
Bring up and down direction adjustment.

• Mute button

• Power On/Off Button
• Input Select Button
(See next page)

• ARC button
Aspect Ratio Correction. Toggles through aspect ratio options.

• Auto Button
Automatic adjustment function
(Operational for the analog signal only)

There is not a function which is supported

There is not a function which is supported

• Exit Button

• Volume ◄ ► Button
Volume up and down

• Check Button

There is not a function which is supported

Name and Function of the Parts

*** The product image in the user's guide could be different from the actual image.**

Rear View



1. **Power Connector : Connect the power cord**
2. **Wired Remote Control Port**
3. **RS-232C Serial Ports**
4. **RGB, HDMI/DVI Ports**
5. **PC Sound Jack**
   : Connect the audio cable to the *LINE OUT jack of the PC sound card.
6. **AV Ports**
7. **Speaker Ports**

***LINE OUT**

A terminal used to connect to the speaker including a built-in amplifier (Amp). Make sure that the connecting terminal of the PC sound card is checked before connecting. If the Audio Out of PC sound card has only Speaker Out, reduce the PC volume.

If the Audio Out of the PC sound card supports both Speaker Out and Line Out, convert to Line Out using the card jumper of the program (Refer to the Sound Card Manual).

Connecting to External Devices

When Connecting to your PC

1 First of all, see if the computer, product and the peripherals are turned off. Then, connect the signal input cable.

(A) When connecting with the D-Sub signal input cable.

(B) When connecting with the HDMI to DVI signal input cable (not included).



* User must use shielded signal interface cables (D-sub 15 pin cable, DVI cable) with ferrite cores to maintain standard compliance for the product.

2 Connect the Audio cable.

3 Connect the power cord.



Connecting to External Devices

4 **(1) Turn on power by pressing the power button on the product.**

(2) Turn on the PC.

5 **Select an input signal.**
Press the INPUT button on the remote control to select the input signal.

INPUT → ▼▲ → SET

Or, press the INPUT botton on the bottom of the product.

INPUT → ▼▲ → AUTO/SET

(A) When connecting with a D-Sub signal input cable.
• Select **RGB PC** : 15-pin D-Sub analog signal.

(B) When connecting with a HDMI to DVI signal input cable.
• Select **HDMI/DVI** : HDMI to DVI Digital signal.



Note

- **How to connect to two computers.**
  Connect the signal cables (HDMI to DVI and D-Sub) to each computer.
  Press the INPUT button on the remote control to select the computer to use.
- **Directly connect to a grounded power outlet or power strip (three prong connector.)**

Connecting to External Devices

Daisy Chain Monitors

Use this function when displaying ANALOG RGB inputs of a PC to the other product.

- **To use different products connected to each other**
  Connect one end of the signal input cable(15-pin D-Sub Signal Cable) to the **RGB OUT** connector of **product 1** and connect the other end to the RGB IN connector of other products.



Note

- When multi-connecting in/out cascade format, no loss cables are recommended. We recommend that you should use cable distributor.

Connecting to External Devices

VESA FDMI wall Mounting

This product supports a VESA FDMI compliant mounting interface. These mounts are purchaed separately and not available from LG. Refer to the instructions included with wall mount for more info.



The Set is equipped with a kensington Securify System connector on the back panel. The cable and lock are available separate and are not sold by LG. For more info, visit http://www.kensington.com, the internet home page of the Kensington company.

WARNING

►To prevent injury, this apparatus must be securely attached to the wall in accordance with the installation instructions.

Optional Installer Remote Control for model No. Series M3702C

There is an optional Installer remote control available for the M3702C Models. The installer remote control is NOT included with the TV.

Option Extras



Wall Mounting Bracket
(AP-WX60)

Connecting to External Devices



Inserting batteries into remote control.



1. **Slide off the battery cover.**
2. **Insert the batteries with correct polarity (+/-).**
3. **Close the battery cover.**
   - Dispose of used batteries in the recycle bin to prevent environmental pollution.

Connecting to External Devices

Video Input

1 Connect the video cable as shown in the below figure and then connect the power cord (See page 10).

A When connecting with a BNC cable.
- Connect the input terminal with a proper color match.



B When connecting with a S-Video cable.
- Connect to the S-Video input terminal to watch high image quality movies.



2 Select an input signal.
Press the INPUT button on the remote control to select the input signal.

INPUT → ▼▲ → SET

Or, press the INPUT botton on the bottom of the product.

INPUT → ▼▲ → AUTO/SET



A When connecting with an BNC cable.
- Select **AV.**

B When connecting with an S-Video cable.
- Select **AV.**

Note
- When the BNC cable is connected simultaneously with S-Video cable, S-Video input has a priority.

Connecting to External Devices

Component Input (480i/480p/576i/576p/720p/1080i)

1 Connect the video/audio cable as shown in the below figure and then, connect the power cord (See page 10).

• Connect the input terminal with a proper color match.



Note
- Some devices may require HDCP in order to display HD signals.
- Component doesn't support HDCP.

2 Select an input signal.
Press the INPUT button on the remote control to select the input signal.

INPUT → ▼▲ → SET

Or, press the INPUT botton on the bottom of the product.

INPUT → ▼▲ → AUTO/SET

Ⓐ • Select **Component 1**

Ⓑ • Select **Component 2**

Input
AV
∨Component1
Component2
RGB PC
HDMI/DVI
▲▼ ⊙

Input
AV
Component1
∨Component2
RGB PC
HDMI/DVI
▲▼ ⊙

Connecting to External Devices

HDMI Input (480p/576p/720p/1080i/1080p)

-HDMI Supports High Definition input and HDCP (High-bandwidth Digital Content Protection). Some devices require HDCP in order to display HD signals.

1 Connect the video/audio cable as shown in the below figure and then connect the power cord (See page 10).



Note : Dolby Digital is not supported.

2 Select an input signal.
Press the INPUT button on the remote control to select the input signal.

INPUT → ▼▲ → SET

Or, press the INPUT botton on the bottom of the product.

INPUT → ▼▲ → AUTO/SET

When connecting with a HDMI to DVI signal input cable.
When connecting with a HDMI signal input cable.
• Select **HDMI/DVI**



Connecting to External Devices

Watching AV Outputs

- When using AV input, you can connect the AV Out to other monitors.



Note

- When multi-connecting in/out cascade format, no loss cables are recommended. We recommend that you should use cable distributor.

User Menus

Screen Adjustment options



1	**Power Button**	• Press this button to turn on the power. Press this button again to turn it off.
2	**Power Indicator**	• This Indicator lights up green when the display operates normally (on mode). If the display is in sleep (Energy Saving) mode, this indicator color changes to amber.
3	**MENU Button**	• Use this button to show/hide the OSD (On Screen Display) menu screen.
4	**OSD Select / Adjust Button**	• Use this button to select an icon or adjust the setting in the OSD screen.
	▼▲	• Adjust the up and down.
	◀ ▶	• Adjust the volume. Volume 35

User Menus

Screen Adjustment options

5 **AUTO/SET Button**

[For PC Analog signal]

[When XGA Mode is active and 1360 X768 is selected]

6 **INPUT Button**

SOURCE → ▼▲ → AUTO/SET

- Toggles between inputs

AV	Composite Video, Separate Video
Component 1	HDTV, DVD
Component 2	HDTV, DVD
RGB PC	15-pin D-Sub analog signal
HDMI/DVI	Digital signal



7 **IR Receiver**

• This is where the unit receives signals from the remote control.

User Menus

OSD Menu

Icon	Function Description
Picture	Adjusts screen brightness, contrast and color that you prefer.
Audio	Adjusts the audio options.
Time	Adjusts the timer options.
Option	Adjusts the screen status according to the circumstances.
Information	Adjust Set ID and check Serial No. and SW version.

Note

OSD(On Screen Display)
The OSD function enables you to adjust the screen status conveniently since it provides graphical presentation.

User Menus

How to adjust the OSD (On Screen Display) screen



• Use the remote control to adjust the OSD screen.

1. Press the **MENU** Button, then the main menu of the OSD appears.
2. To access a control, use the ▼ ▲ Buttons.
3. When the icon you want becomes highlighted, press the **SET** Button.
4. Use the ▼ ▲ ◄ ► Buttons to adjust the item to the desired level.
5. Accept the changes by pressing the **SET** Button.
6. Exit the OSD by pressing the **EXIT** Button.

How to adjust the screen automatically

Press the AUTO/SET button (AUTO button on a remote Control) in the PC analog signal. Then optimal screen settings will be selected that fit into the current mode. If adjustment is not satisfactory, you can adjust the screen manually.

[When XGA Mode is active and 1360 X768 is selected]

User Menus

Adjusting Screen Color

Picture Mode



Toggles between screen presets.

- **Vivid** : Select this option to display with a sharp image.
- **Standard** : The most general and natural screen display status.
- **Cinema** : Select this option to lower brightness by one level.
- **Sport** : Select this option to display with a soft image.
- **Game** : To enjoy dynamic image when playing a game.
- **User1,2** : Select this option to use the user-defined settings.



Backlight : To control the brightness of the screen,adjust the brightness of LCD panel.
Contrast : Adjust the difference between the light and dark levels in the picture.
Brightness : To adjust the brightness of the screen.
Color : To adjust the color to desired level.
Sharpness : To adjust the clearness of the screen.
Tint :To adjust the tint to desired level.
Expert : To compensate for each image mode, or adjust image values according to a particular image. (Applied only to User2 menu.)

Note

If the '**Picture Mode**' setting in the **Picture**menu is set to **Vivid, Standard, Cinema, Sport** or **Game** the subsequent menus will be automatically set.

Adjusting Screen Color

Color Temperature



Color Settings

- **Cool** : Slightly purplish white.
- **Medium** : Slightly bluish white.
- **Warm** : Slightly reddish white.
- **User** : Select this option to use the user-defined settings.



Red / Green / Blue
Set your own color levels.

Adjusting Screen Color

Advanced



- **Gamma** : Set your own gamma value. : -50/0/50
  On the monitor, high gamma values display whitish images and low gamma values display high contrast images.
- **Film Mode** : (Function works in the following mode - AV, Component 480i/576i)
  When you watch a movie, this function adjusts the set to the best picture appearance.
- **Black Level** : (Function works in the following mode - AV(NTSC), HDMI/DVI
  adjusts the contrast and the brightness of the screen using the black level of the screen.

  - **Low :** The reflection of the screen gets brighter.
  - **High :** The reflection of the screen gets darker.

- **NR :** Removing the noise up to the point where it does not damage the original picture.

Adjusting Screen Color

Aspect Ratio To select the image size of the screen.



<AV>

16:9 Widescreen mode.

Just Scan Allows you to enjoy the transmitted data fully without any images cut off. (* This menu is activated only in 720p, 1080p and 1080i in Component mode.)

Original The aspect ratio is not adjusted from the original. It is set by the program being watched.

4:3 This picture format is 4:3 aspect ratio.

1:1 The aspect ratio is not adjusted from the original. Used in PC mode. (Only HDMI/ DVI PC, RGB PC)

14:9 14:9 programs are viewed normally in 14:9 with black bars added to the top and bottom. 4:3 programs are magnified on the top/bottom and left/right sides.

Zoom1, 2 4:3 programes are magnified until they fill the 16:9 screen. The top and bottom will be cut off.

ARC \ MODE	AV	Component	HDMI/DVI		RGB
			DTV	PC	PC
16:9	●	●	●	●	●
Just Scan	×	●	●	×	×
Original	●	×	×	×	×
4:3	●	●	●	●	●
1:1	×	×	×	●	●
14:9	●	×	×	×	×
Zoom1	●	×	×	×	×
Zoom2	●	×	×	×	×

Adjusting Screen Color

Picture Reset Return **Picture Mode**, **Color Temperature**, **Advanced** to the default factory settings.



Screen Adjust the screen video.



Auto Config. (RGB PC input only) : This button is for the automatic adjustment of the screen position, clock and phase. This function is available for analog signals only.
Manual Config. : If the picture isn't clear after auto adjustment and characters are still trembling, adjust the picture phase manually.
* Phase, Clock function are not available in Component, HDMI/DVI DTV.)

Clock : To minimize any vertical bars or stripes visible on the screen background. The horizontal screen size will also change. This function is available for analog signals only.
Phase : To adjust the focus of the display. This item allows you to remove any horizontal noise and clear or sharpen the image of characters. This function is available for analog signals only.
H-Position : Moving the screen position horizontally.
V-Position : Moving the screen position vertically.

H-Size : Adjust the horizontal size of the screen.

V-Size : Adjust the vertical size of the screen.

XGA Mode (RGB-PC only). : For more improved or better picture quality, select the same mode corresponding to computer resolution.

Reset: Return **Manual config.** to the default factory settings.

Adjusting the audio function

Sound Mode

The best sound tone quality will be selected automatically depending on the video type that you're currently watching.



- **Clear Voice** : By differentiating the human sound range from others,it helps users listen to human voices better.
- **Standard** : The most commanding and natural audio.
- **Music** : Select this option to enjoy the original sound when listening to the music.
- **Cinema** : Select this option to enjoy sublime sound.
- **Sport** : Select this option to watch sports broadcasting.
- **Game** : To enjoy dynamic sound when playing a game.
- **User** : Select this option to use the user-defined audio settings.



Auto Volume

To adjust uneven sound volumes across all channels or signals automatically to the most appropriate level. To use this feature, select On.

Balance

Use this function to balance sound from the left and right speakers.

Speaker

You can adjust internal speaker status.
If you want to use your external hi-fi stereo system, turn off the internal speakers of the set.

Note

When connected to your computer and the **'Sound Mode'** setting in the audio menu is **Clear Voice, Standard**, **Music**, **Cinema** or **Sport**, the available menus are **Balance, Auto Volume, Speaker**.

Adjusting the timer function



Clock If the current time is incorrect, reset the clock manually.
1) Press the **MENU** button and then use ▼▲ button to select the **Time** menu.
2) Press the ▶ button and then use ▼▲ button to select the **Clock** menu.
3) Press the ▶ button and then use ▼▲ button to set the hour(00~23).
4) Press the ▶ button and then use ▼▲ button to set the minutes(00~59).

On/Off Timer The off time automatically switches the set to standby at the pre-set time.
1) Press the **MENU** button and then use ▼▲ button to select the **Time** menu.
2) Press the ▶ button and then use ▼▲button to select **On/Off Timer**.
3) Press the ▶ button and then use ▼▲button to set the hour(00~23).
4) Press the ▶ button and then use ▼▲button to set the minutes(00~59).
5) Press the ▶ button and then use ▼▲button to select **On** or **Off**.

Sleep Time The power is automatically turned off when the time set by a user is passed.
1) Press the **MENU** button and then use ▼▲ button to select the **Sleep Time** menu.
2) Press the ▶ button and then use ▼▲ button to set the hour(00~23).
3) Press the ▶ button and then use ▼▲ button to set the minutes(00~59).

Auto Sleep If **Auto Sleep** is active and there is no input signal, the set switches to off mode automatically after 10 minutes.
1) Press the **MENU** button and then use ▼▲ button to select the **Auto Sleep** menu.
2) Press the ▶ button and then use ▼▲ button to select **On** or **Off**.

Power On Delay When connecting multiple monitors and turning the power on, the monitors are turned on individually to prevent overload.

Note

- In the event of power interruption (disconnection or power failure), the clock must be reset.
- Once the on or off time is set, these functions operate daily at the preset time.
- Off time function overrides On time function if they are set to the same time.
- When On time is operated, input screen is turned on as it was turned off.

User Menus

Selecting the options



Language To choose the language in which the control names are displayed.

Key Lock Use the ▼ ▲ buttons to select **On** or **Off**. The monitor can be set up so that it can only be used with the remote control. This feature can prevent unauthorized viewing.

In order to lock the OSD screen adjustment, set the **Key Lock** tab to the '**On**' position.
In order to unlock it, do the following :
• Push the **MENU** button on the remote control and set **Key Lock** to the '**Off**' position.

ISM Method A frozen or still picture from a PC/Video game displayed on the screen for prolonged periods could result in a ghost image remaining even when you change the image. Avoid allowing a fixed image to remain on the screen for a long period of time.

Normal : Leave on normal if you don't foresee image burn in being a problem.

White wash : White wash fills the screen with solid white. This helps removes permanent images burned into the screen. A permanent image may be impossible to clear entirely with white wash.

Orbiter : May help prevent ghost images. However, it is best not to allow any fixed image to remain on the screen. To avoid a permanent image on the screen, the screen will move every 2 minutes.

Inversion : This function inverts the panel color of the screen. The panel color is automatically inverted every 30 minutes.

Dot Wash : This function moves the black dots of the screen. The black dots is automatically moved every 5 second.

Power Indicator Use this function to set the power indicator on the front side of the product to **On** or **Off**.

Logo Light Use this function to set the Logo Light on the front side of the product to **On** or **Off**.

DPM Select A user can choose to turn the power saving mode on / off.

Selecting the options

• To use this function

- Must be displayed with various other products.
- Must be in a function that can be connected to RS-232C or RGB Out

Tile mode



It is used to enlarge the screen and also used with several products to view screen.

• Tile Mode

Tile mode and choose Tile alignment and set the ID of the current product to set location.

* Only after pressing the SET button the adjustments made to the settings will be saved.

- Tile mode : row x column (r = 1, 2, 3, 4,5 c = 1, 2, 3, 4,5)
- 5 x 5 available.
- Configuration of an integration screen is also available as well as configuration of One by one Display.

- Tile mode (product 1 ~ 4) : r(2) x c(2)



Selecting the options

- Tile mode (product 1 ~ 9) : r(3) x c(3)



- Tile mode (product 1 ~ 2) : r(2) x c(1)



- Tile mode (product 1 ~16) : r(4) x c(4)



Selecting the options

Tile mode



- **H-Size** Adjust the horizontal size of the screen taking into account the size of the bezel.
- **V-Size** Adjust the vertical size of the screen taking into account the size of the bezel.
- **H-Position** Moving the screen position horizontally.
- **V-Position** Moving the screen position vertically.
- **Reset** Function to initialize and release Tile.
  All Tile setting are released when selecting Tile recall and the screen returns to Full screen.
- **Tile ID** Select the location of the Tile by setting an ID.
- **Natural** The image is omitted by the distance between the screens to be naturally shown.

Factory Reset Select this option to return to the default factory settings.

Adjust Set ID and check Serial No. and SW version.

Set ID You can assign a unique **Set ID** NO (name assignment) to each product when several products are connected for display. Specify the number (1~99) using the ▼ ▲ button and exit. Use the assigned **Set ID** to individually control each product using the Product Control Program.

Serial No. This menu shows the serial number of the product.

SW Version This menu shows the software version.

Troubleshooting

No image is displayed

● Is the product power cord connected?	• See if the power cord is properly connected to the outlet.
● Is the power indicator light on?	• See if the power switch is turned on. • May need service.
● Power is on, power indicator is blue but the screen appears extremely dark.	• Adjust brightness and contrast again. • Backlight may need repair.
● the power indicator amber?	• If the product is in power saving mode, move the mouse or press any key. • Turn both devices off and then back on.
● Does the 'Out of range' message appear?	• The signal from the PC (video card) is out of the vertical or horizontal frequency range of the product. Adjust the frequency range by referring to the Specifications in this manual. *** Maximum resolution** RGB : 1600 x 1200 @60Hz HDMI/DVI : 1920 x 1080 @60Hz
● Does the 'Check signal cable' message appear?	• The signal cable between PC and product is not connected. Check the signal cable. • Press the 'INPUT' menu in the remote Control to check the input signal.

'Unknown Product' message appears when the product is connected.

● Did you install the driver?	• Install the product driver, which is provided with the product, or download it from the web site. (http://www.lge.com) • See if the plug&play function is supported by referring to the video card user manual.

'Key Lock On' message appears.

● The 'Key Lock On' message appears when pressing the Menu button.	• The control locking function prevents unintentional OSD setting change due to careless usage. To unlock the controls, simultaneously press the Menu button and ▶button for several seconds. (You cannot set this function using the remote control buttons. You can set this function in the product only.)

Note

*** Vertical frequency:** To enable the user to watch the product display, screen image should be changed tens of times every second like a fluorescent lamp. The vertical frequency or refresh rate is the times of image display per second. The unit is Hz.

*** Horizontal frequency:** The horizontal interval is the time to display one vertical line. When 1 is divided by the horizontal interval, the number of horizontal lines displayed every second can be tabulated as the horizontal frequency. The unit is kHz.

Troubleshooting

The screen image looks abnormal.

● **Is the screen position wrong?**	• D-Sub analog signal – Press the “AUTO” button in the remote control to automatically select the optimal screen status that fits into the current mode. If adjustment is not satisfactory, use the Position OSD menu. • See if the video card resolution and frequency are supported by the product. If the frequency is out of range, set to the recommended resolution in the Control Panel – Display – Setting menu.
● **Do thin lines appear on the background screen?**	• D-Sub analog signal – Press the “AUTO” button in the remote control to automatically select an optimal screen status that fits into the current mode. If adjustment is not satisfactory, use the Clock OSD menu.
● **Horizontal noise appears or the characters look blurred.**	• D-Sub analog signal – Press the “AUTO” button in the remote control to automatically select an optimal screen status that fits into the current mode. If adjustment is not satisfactory, use the Phase OSD menu.
● **The screen is displayed abnormally.**	• The proper input signal is not connected to the signal port. Connect the signal cable that matches with the source input signal.

After-image appears on the product.

● **After-image appears when the product is turned off.**	• If you use a fixed image for a long time, the pixels may be damaged quickly. Use the screen-saver function.

Troubleshooting

The audio function does not work.

● No sound?	• See if the audio cable is connected properly. • Adjust the volume. • See if the sound is set properly.
● Sound is too dull.	• Select the appropriate equalize sound.
● Sound is too low.	• Adjust the volume.

Screen color is abnormal.

● Screen has poor color resolution (16 colors).	• Set the number of colors to more than 24 bits (true color) Select Control Panel – Display – Settings – Color Table menu in Windows.
● Screen color is unstable or mono-colored.	• Check the connection status of the signal cable. Or, re-insert the PC video card.
● Do black spots appear on the screen?	• Several pixels (red, green, white or black color) may appear on the screen, which can be attributable to the unique characteristics of the LCD panel. It is not a malfunction of the LCD.

Specifications

The product specifications can change without prior notice for product improvement.

LCD Panel	37 inches Visible diagonal (94.0 cm)TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel 0.6000 mm X 0.6000 mm (Pixel Pitch)
Power	**Rated Voltage** AC 100-240V~ 50/60Hz 1.8A **Power Consumption** On Mode : 180W Sleep Mode : ≤ 1W (RGB) / 4W(HDMI/DVI) Off Mode : ≤ 1W
Dimensions &Weight	**[1]** **[2]**  Width x Height x Depth **[1]** 92.81 cm (36.54 inches) x 57.12 cm (22.49 inches) x 11.25 cm (4.43 inches) **[2]** 92.81 cm (36.54 inches) x 57.12 cm (22.49 inches) x 11.25 cm (4.43 inches) **Net** **[1]** 20.76 kg (45.77 lbs) **[2]** 21.54 kg (47.49 lbs)

NOTE

- Information in this document is subject to change without notice.

Specifications

The product specifications can change without prior notice for product improvement.

Video Signal	**Max. Resolution**	RGB : 1600 X 1200 @60Hz HDMI/DVI : 1920 X 1080 @60Hz – It may not be supported depending on the OS or video card type.
	Recommended Resolution	RGB : WSXGA 1360 X 768 @60Hz HDMI/DVI : WSXGA 1360 X 768 @60Hz – It may not be supported depending on the OS or video card type.
	Horizontal Frequency	RGB : 30 - 83 kHz HDMI/DVI : 30 - 83 kHz
	Vertical Frequency	RGB : 56 - 75 Hz HDMI/DVI : 56 - 60 Hz
	Synchronization Type	Separate/Composite/Digital
Input Connector		15-pin D-Sub type, HDMI (digital), S-Video, Composite Video, Component, RS-232C
Environmental Conditions	**Operational Condition** **Storage Condition**	Temperature: 0˚C ~ 40˚C , Humidity: 10% ~ 80% Temperature: -20˚C ~ 60˚C , Humidity: 5% ~ 90%

*** Applicable only for models that support the speakers**

Audio	RMS Audio Output	10W+10W(R+L)
	Input Sensitivity	0.7Vrms
	Speaker Impedance	8Ω

NOTE

- Information in this document is subject to change without notice.

Specifications

PC Mode – Preset Mode

Preset mode		Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Preset mode		Horizontal Frequency (kHz)	Vertical Frequency (Hz)
1	640 x 350	31.469	70.8	*11	1280 x 768	47.7	60
2	720 x 400	31.468	70.8	*12	1360 x 768	47.72	59.799
*3	640 x 480	31.469	59.94	*13	1366 x 768	47.7	60
4	640 x 480	37.5	75	*14	1280 x 1024	63.981	60.02
*5	800 x 600	37.879	60.317	15	1280 x 1024	79.98	75.02
6	800 x 600	46.875	75	16	1600 x 1200	75.00	60
7	832 x 624	49.725	74.55	*17	1920 x 1080	67.5	60
*8	1024 x 768	48.363	60				
9	1024 x 768	60.123	75.029				
*10	1280 x 720	44.772	59.855				

1~16 : RGB mode
* : HDMI/DVI mode

DTV Mode

	Component	HDMI/DVI(DTV)
480i	o	x
576i	o	x
480p	o	o
576p	o	o
720p	o	o
1080i	o	o
1080p	x	o

Power Indicator

Mode	Product
On Mode	Green
Sleep Mode	Amber
Off Mode	-

NOTE

- DTV/PC selection on HDMI/DVI inputs is available for PC resolutions : 640 X 480/60Hz, 1280 X 720/60Hz and DTV resolutions : 480p, 720p.

Controlling the Multiple Product

Use this method to connect several products to a single PC.
You can control several products at a time by connecting them to a single PC.

Connecting the cable

Connect the RS-232C cable as shown in the picture.

* The RS-232C protocol is used for communication between the PC and product. You can turn the product on/off, select an input source or adjust the OSD menu from your PC.



RS-232C Configurations

7-Wire Configurations (Standard RS-232C cable)

PC		Monitor	
RXD	2 —	3	TXD
TXD	3 —	2	RXD
GND	5 —	5	GND
DTR	4 —	6	DSR
DSR	6 —	4	DTR
RTS	7 —	8	CTS
CTS	8 —	7	RTS
	D-Sub 9 (Female)	D-Sub 9 (Female)	

3-Wire Configurations (Not Standard)

PC		Monitor	
RXD	2 —	3	TXD
TXD	3 —	2	RXD
GND	5 —	5	GND
DTR	4	6	DSR
DSR	6	4	DTR
RTS	7	8	RTS
CTS	8	7	CTS
	D-Sub 9 (Female)	D-Sub 9 (Female)	

Communication Parameter

- ▶ Baud Rate : 9600buadRate (UART)
- ▶ Data Length : 8bits
- ▶ Parity Bit : None
- ▶ Stop Bit : 1bit
- ▶ Flow Control : None
- ▶ Communication Code : ASCII code
- ▶ Use a crossed (reverse) cable

Command Reference List

	COMMAND1	COMMAND2	DATA1	DATA2	DATA3
01. Power	k	a	00H - 01H		
02. Input Select	k	b	02H - 09H		
03. Aspect Ratio	k	c	01H - 09H		
04. Screen Mute	k	d	00H - 01H		
05. Volume Mute	k	e	00H - 01H		
06. Volume Control	k	f	00H - 64H		
07. Contrast	k	g	00H - 64H		
08. Brightness	k	h	00H - 64H		
09. Color	k	i	00H - 64H		
10. Tint	k	j	00H - 64H		
11. Sharpness	k	k	00H - 64H		
12. OSD Select	k	l	00H - 01H		
13. Remote Lock/ key Lock	k	m	00H - 01H		
14. Balance	k	t	00H - 64H		
15. Color Temperature	k	u	00H - 03H		
16. Abnomal state	k	z	FFH		
17. ISM mode	j	p	00H - 10H		
18. Auto configuration	j	u	01H		
19. Key	m	c	Key Code		
20. Tile Mode	d	d	00H - 55H		
21. Tile H Size	d	g	00H - 64H		
22. Tile V Size	d	h	00H - 64H		
23. Tile ID Set	d	i	00H - 19H		
24. Natural Mode (In Tilemode)	d	j	00H - 01H		
25. Elapsed time return	d	l	FFH		
26. Temperature value	d	n	FFH		
27. Lamp fault check	d	p	FFH		
28. Auto Volume	d	u	00H - 01H		
29. Speaker	d	v	00H - 01H		
30. Time	f	a	00H - 06H	00H - 17H	00 - 3BH
31. On Timer (On/Off Timer) On, Off	f	b	00H, FFH	00H - FFH	
32. Off Timer (On/Off Timer) On, Off	f	c	00H, FFH	00H - FFH	
33. On Timer (On/Off Timer) Time	f	d	00H - 07H	00H - 17H	00 - 3BH
34. Off Timer (On/Off Timer) Time	f	e	00H - 07H	00H - 17H	00 - 3BH
35. Sleep Time	f	f	00H - 08H		
36. Auto Sleep	f	g	00H - 01H		
37. Power On Delay	f	h	00H - 64H		
38. Language	f	i	00H - 09H		
39. DPM Select	f	j	00H - 01H		
40. Reset	f	k	00H - 02H		
41. S/W Version	f	z	FFH		
42. Input Select	x	b	20H - A0H		

Transmission / Receiving Protocol

Transmission

[Command1][Command2][ ][Set ID][ ][Data][Cr]

* [Command 1]: First command. (k)
* [Command 2]: Second command.(a ~ u)
* [Set ID]: Set up the Set ID number of product.
  range : 1~99. by setting '0', server can control all products.
  * In case of operating with more than 2 sets using set ID as '0' at the same time, it should not be checked the ack message.
  Because all sets will send the ack message, so it's impossible the check the whole ack messages.
* [DATA]: To transmit command data.
  Transmit 'FF' data to read status of command.
* [Cr]: Carriage Return
  ASCII code '0x0D'
* [ ]: ASCII code Space (0x20)'

OK Acknowledgement

[Command2][ ][Set ID][ ][OK][Data][x]

* The Product transmits ACK (acknowledgement) based on this format when receiving normal data. At this time, if the data is data read mode, it indicates present status data. If the data is data write mode, it returns the data of the PC computer.

Error Acknowledgement

[Command2][ ][Set ID][ ][NG][Data][x]

* If there is error, it returns NG

Transmission / Receiving Protocol

01. Power(Command : a)

▶ To control Power On/Off of the Set.

Transmission

[k][a][ ][Set ID][ ][Data][Cr]

Data 0 : Power Off 1 : Power On

Acknowledgement

[a][ ][Set ID][ ][OK][Data][x]

▶To show the status of Power On/Off.

Transmission

[k][a][ ][Set ID][ ][FF][Cr]

Acknowledgement

[a][ ][Set ID][ ][OK][Data][x]

Data 0 : Power Off 1 : Power On

02. Input Select (Command : b) (Main Picture Input)

▶ To select input source for the Set.
You can also select an input source using the INPUT button on the remote control.

Transmission

[k][b][ ][Set ID][ ][Data][Cr]

Data 2 : AV
4 : Component 1
5 : Component 2
7 : RGB (PC)
8 : HDMI (DTV)
9 : HDMI (PC)

Acknowledgement

[b][ ][Set ID][ ][OK][Data][x]

Data 2 : AV
4 : Component 1
5 : Component 2
7 : RGB (PC)
8 : HDMI (DTV)
9 : HDMI (PC)

Transmission / Receiving Protocol

03. Aspect Ratio(Command : c) (Main picture format)

▶To adjust the screen format.
You can also adjust the screen format using the ARC (Aspect Ratio Control) button on remote control or in the Screen menu.

Transmission

[k][c][ ][Set ID][ ][Data][Cr]

Data 1 : Normal Screen (4:3)
2 : Wide Screen (16 :9)
4 : Zoom1
5 : Zoom2
6 : Original
7 :14:9
9 : Just Scan(HD DTV), 1:1 (RGB PC, HDMI/DVI PC)

Acknowledgement

[c][ ][Set ID][ ][OK][Data][x]

04. Screen Mute(Command : d)

▶To select screen mute on/off.

Transmission

[k][d][ ][Set ID][ ][Data][Cr]

Data 0 : Screen mute off (Picture on)
1 : Screen mute on (Picture off)

Acknowledgement

[d][ ][Set ID][ ][OK][Data][x]

Transmission / Receiving Protocol

05. Volume Mute(Command : e)

▶ To control On/Off of the Volume Mute.

Transmission

[k][e][ ][Set ID][ ][Data][Cr]

Data 0 : Volume Mute On (Volume Off)
1 : Volume Mute Off (Volume On)

Acknowledgement

[e][ ][Set ID][ ][OK][Data][x]

Data 0 : Volume Mute On (Volume Off)
1 : Volume Mute Off (Volume On)

06. Volume Control(Command : f)

▶ To adjust Volume .

Transmission

[k][f][ ][Set ID][ ][Data][Cr]

Data Min : 00H ~ Max : 64H
(Hexadecimal code)

Acknowledgement

[f][ ][Set ID][ ][OK][Data][x]

Data Min : 00H ~ Max : 64H

• Refer to 'Real data mapping' page A7.

Transmission / Receiving Protocol

07. Contrast(Command : g)

▶ To adjust screen contrast.
You can also adjust the contrast in the Picture menu.

Transmission

[k][g][ ][Set ID][ ][Data][Cr]

Data Min : 00H ~ Max : 64H
• Refer to 'Real data mapping' as shown below.

Acknowledgement

[g][ ][Set ID][ ][OK][Data][x]

* Real data mapping
0 : Step 0
:
A : Step 10
:
F : Step 15
10 : Step 16
:
64 : Step 100

08. Brightness(Command : h)

▶ To adjust screen brightness.
You can also adjust the brightness in the Picture menu.

Transmission

[k][h][ ][Set ID][ ][Data][Cr]

Data Min : 00H ~ Max : 64H
• Refer to 'Real data mapping' as shown below.

Acknowledgement

[h][ ][Set ID][ ][OK][Data][x]

* Real data mapping
0 : Step
:
A : Step 10
:
F : Step 15
10 : Step 16
:
64 : Step 100

Transmission / Receiving Protocol

09. Color(Command : i) (Video only)

▶ To adjust the screen color.
You can also adjust the color in the Picture menu.

Transmission

[k][i][ ][Set ID][ ][Data][Cr]

Data Min : 00H ~ Max : 64H
(Hexadecimal code)

• Refer to 'Real data mapping' page A7.

Acknowledgement

[i][ ][Set ID][ ][OK][Data][x]

Data Min : 00H ~ Max : 64H

10. Tint(Command : j) (Video only)

▶ To adjust the screen tint.
You can also adjust the tint in the Picture menu.

Transmission

[k][j][ ][Set ID][ ][Data][Cr]

Data Red: 00H ~ Green: 64H
(Hexadecimal code)

• Refer to 'Real data mapping' page A7.

Acknowledgement

[j][ ][Set ID][ ][OK][Data][x]

Data Red: 00H ~ Green: 64H

* Tint Real data mapping
0 : Step -50
:
64 : Step 50

Transmission / Receiving Protocol

11. Sharpness(Command : k) (Video only)

▶ To adjust the screen Sharpness.
You can also adjust the sharpness in the Picture menu.

Transmission

[k][k][ ][Set ID][ ][Data][Cr]

Data Min : 00H ~ Max : 64H
(Hexadecimal code)

• Refer to 'Real data mapping' page A7.

Acknowledgement

[k][ ][Set ID][ ][OK][Data][x]

Data Min : 00H ~ Max : 64H

12. OSD Select(Command : l)

▶ To control OSD on/off to the set.

Transmission

[k][l][ ][Set ID][ ][Data][Cr]

Data 0 : OSD Off 1 : OSD On

Acknowledgement

[l][ ][Set ID][ ][OK][Data][x]

Data 0 : OSD Off 1 : OSD On

13. Remote Lock /Key Lock (Command : m)

▶ To control Remote Lock on/off to the set.
This function, when controlling RS-232C, locks the remote control and the local keys.

Transmission

[k][m][ ][Set ID][ ][Data][Cr]

Data 0 : Off 1 : On

Acknowledgement

[m][ ][Set ID][ ][OK][Data][x]

Data 0 : Off 1 : On

Transmission / Receiving Protocol

14 Balance(Command : t)

▶ To adjust the sound balance.

Transmission

[k][t][ ][Set ID][ ][Data][Cr]

Data Min : 00H ~ Max : 64H
(Hexadecimal code)

• Refer to 'Real data mapping' page A7.

Acknowledgement

[t][ ][Set ID][ ][OK][Data][x]

Data Min : 00H ~ Max : 64H

* Balance : L50 ~ R50

15. Color Temperature (Command : u)

▶ To adjust the screen color temperature.

Transmission

[k][u][ ][Set ID][ ][Data][Cr]

Data 0 : Medium
1 : Cool
2 : Warm
3 : User

Acknowledgement

[u][ ][Set ID][ ][OK][Data][x]

Data 0 : Medium
1 : Cool
2 : Warm
3 : User

Transmission / Receiving Protocol

16. Abnomal state (Command : z)

▶ Abnormal State : Used to Read the power off status when Stand-by mode.

Transmission

[k][z][ ][Set ID][ ][Data][Cr]

Data FF : Read
0 : Normal (Power on and signal exist)
1: No signal (Power on)
2 : Turn the monitor off by remote control
3 : Turn the monitor off by sleep time function
4 : Turn the monitor off by RS-232C function
8 : Turn the monitor off by off time function
9 : Turn the monitor off by auto off function

Acknowledgement

[z][ ][Set ID][ ][OK][Data][x]

17. ISM mode(Command: j p)

▶ Used to select the afterimage preventing function.

Transmission

[j][p][ ][Set ID][ ][Data][Cr]

Data 1H : Inversion
2H : Orbiter
4H : White Wash
8H : Normal
10H : Dot Wash

Acknowledgement

[p][ ][Set ID][ ][OK][Data][x]

Transmission / Receiving Protocol

18. Auto Configure(Command: j u)

▶ To adjust picture position and minimize image shaking automatically. it works only in RGB(PC) mode.

Transmission

[j][u][ ][Set ID][ ][Data][Cr]

Data 1 : To set

Acknowledgement

[u][ ][Set ID][ ][OK][Data][x]

19. Key(Command : m c)

▶ To send IR remote key code.

Transmission

[m][c][ ][Set ID][ ][Data][Cr]

Data Key code : Refer to page A18.

Acknowledgement

[c][ ][Set ID][ ][OK][Data][x]

Transmission / Receiving Protocol

20. Tile Mode(Command : d d)

▶ Change a Tile Mode.

Transmission

[d][d][][Set ID][][Data][x]

Data	Description
00	Tile mode is off.
12	1 x 2 mode(column x row)
13	1 x 3 mode
14	1 x 4 mode
...	...
55	5 x 5 mode

* The data can not be set to 0X or X0 except 00.

Acknowledgement

[d][][00][][OK/NG][Data][x]

Transmission / Receiving Protocol

21. Tile H Size(Command : d g)

▶To set the Horizontal size.

Transmission

[d][g][][Set ID][][Data][x]

Data Min : 00H ~ Max : 64H

Acknowledgement

[g][][Set ID][][OK/NG][Data][x]

22. Tile V Size(Command : d h)

▶To set the Vertical size.

Transmission

[d][h][][Set ID][][Data][x]

Data Min : 00H ~ Max : 64H

Acknowledgement

[h][][Set ID][][OK/NG][Data][x]

Transmission / Receiving Protocol

23. Tile ID Set(Command : d i)

▶ To assign the Tile ID for Tiling function .

Transmission

[d][i][][Set ID][][Data][x]

Data Min : 00H ~ Max : 19H
(Hexadecimal code)

Acknowledgement

[i][][Set ID][][OK/NG][Data][x]

24 Natural Mode (In Tilemode) (Command : d j)

▶ The image is omitted by the distance between the screens to be naturally shown.

Transmission

[d][j][][Set ID][][Data][x]

Data 0 : Natural Off
1 : Natural On
ff : Read Status

Acknowledgement

[j][][Set ID][][OK/NG][Data][x]

25. Elapsed time return(Command : d l)

▶ To read the elapsed time.

Transmission

[d][l][][Set ID][][Data][x]

* The data is always FF(in Hex).

Acknowledgement

[l][][Set ID][][OK/NG][Data][x]

* The data means used hours.
(Hexadecimal code)

Transmission / Receiving Protocol

26. Temperature value (Command : d n)

▶ To read the inside temperature value.

Transmission

[d][n][][Set ID][][Data][x]

* The data is always FF(in Hex).

Acknowledgement

[n][][Set ID][][OK/NG][Data][x]

* The data is 1 byte long in Hexadecimal.

27. Lamp fault Check(Command : d p)

▶ To check lamp fault.

Transmission

[d][p][][Set ID][][Data][x]

* The data is always FF(in Hex).

Acknowledgement

[p][][Set ID][][OK/NG][Data][x]

Data 0 : Lamp Fault
1: Lamp OK

Transmission / Receiving Protocol

28. Auto volume (Command : d u)

▶ Automatically adjust the volume level.

Transmission

[d][u][][Set ID][][Data][x]

Data 0 : Off
1 : On

Acknowledgement

[u][][Set ID][][OK/NG][Data][x]

29. Speaker (Command : d v)

▶ Turn the speaker on or off.

Transmission

[d][v][][Set ID][][Data][x]

Data 0 : Off
1 : On

Acknowledgement

[v][][Set ID][][OK/NG][Data][x]

Transmission / Receiving Protocol

30. Time (Command : f a)

▶ Set the current time.

Transmission

[f][a][][Set ID][][Data1][][Data2][][Data3][Cr]

[Data1]
0 : Monday
1: Tuesday
2 : Wednesday
3 : Thursday
4 : Friday
5 : Saturday
6 : Sunday

[Data2]
0H~17H (Hours)

[Data3]
00H~3BH (Minutes)

Acknowledgement

[a][][Set ID][][OK/NG][Data1][Data2][Data3][x]

*When reading data, FFH is inputted for [Data1], [Data2] and [Data3].
In other cases, all are treated as NG.

Transmission / Receiving Protocol

31. On Timer (On/Off Timer) On, Off (Command : F b)

▶ Set days for On Timer.

Transmission

[f][b][][Set ID][][Data1][][Data2][Cr]

[Data1]
0 (Write), FFH(Read)

[Data2]
00H~FFH
bit0 : Monday On Timer On(1), Off(0)
bit1 : Tuesday On Timer On(1), Off(0)
bit2 : Wednesday On Timer On(1), Off(0)
bit3 : Thursday On Timer On(1), Off(0)
bit4 : Friday On Timer On(1), Off(0)
bit5 : Saturday On Timer On(1), Off(0)
bit6 :Sunday On Timer On(1), Off(0)
bit7 : Everyday On Timer On(1), Off(0)

Acknowledgement

[b][][Set ID][][OK/NG][Data1][Data2][x]

32. Off Timer (On/Off Timer) On, Off (Command : f c)

▶ Set days for Off Timer.

Transmission

[f][c][][Set ID][][Data1][][Data2][Cr]

[Data1]
0 (Write), FFH(Read)

[Data2]
00H~FFH
bit0 : Monday Off Timer On(1), Off(0)
bit1 : Tuesday Off Timer On(1), Off(0)
bit2 : Wednesday Off Timer On(1), Off(0)
bit3 : Thursday Off Timer On(1), Off(0)
bit4 : Friday Off Timer On(1), Off(0)
bit5 : Saturday Off Timer On(1), Off(0)
bit6 :Sunday Off Timer On(1), Off(0)
bit7 : Everyday Off Timer On(1), Off(0)

Acknowledgement

[c][][Set ID][][OK/NG][Data1][Data2][x]

Transmission / Receiving Protocol

33. On Timer (On/Off Timer) Time (Command : f d)

▶ Set On Timer.

Transmission

[f][d][][Set ID][][Data1][][Data2][Data3][Cr]

[Data1]
0 : Monday
1: Tuesday
2 : Wednesday
3 : Thursday
4 : Friday
5 : Saturday
6 : Sunday
7 : Everyday

[Data2]
00H~17H (Hours)

[Data3]
00H~3BH (Minutes)

Acknowledgement

[d][][Set ID][][OK/NG][Data1][Data2][Data3][x]

*When reading data, FFH is inputted for [Data2], [Data3].
In other cases, all are treated as NG.

Transmission / Receiving Protocol

34. Off Timer (On/Off Timer) Time (Command : f e)

▶ Set Off Timer.

Transmission

[f][e][][Set ID][][Data1][][Data2][][Data3][Cr]

[Data1]
0 : Monday
1: Tuesday
2 : Wednesday
3 : Thursday
4 : Friday
5 : Saturday
6 : Sunday
7 : Everyday

[Data2]
00H~17H (Hours)

[Data3]
00H~3BH (Minutes)

Acknowledgement

[e][][Set ID][][OK/NG][Data1][Data2][Data3][x]

*When reading data, FFH is inputted for [Data2], [Data3].
In other cases, all are treated as NG.

Transmission / Receiving Protocol

35. Sleep Time (Command : f f)

▶ Set Sleep Time.

Transmission

[f][f][][Set ID][][Data][Cr]

Data
0 : Off
1 : 10
2 : 20
3 : 30
4 : 60
5 : 90
6 : 120
7 : 180
8 : 240
(Orderly)

Acknowledgement

[f][][Set ID][][OK/NG][Data][x]

36. Auto Sleep (Command : f g)

▶ Set Auto Sleep.

Transmission

[f][g][][Set ID][][Data][Cr]

Data 0 : Off
1: On

Acknowledgement

[g][][Set ID][][OK/NG][Data][x]

Transmission / Receiving Protocol

37. Power On Delay (Command : f h)

▶ Set the schedule delay when the power is turned on (Unit: second).

Transmission

[f][h][][Set ID][][Data][Cr]

Data : 00H ~ 64H (Data value)

Acknowledgement

[h][][Set ID][][OK/NG][Data][x]

38. Language (Command : f i)

▶ Set the OSD language.

Transmission

[f][i][][Set ID][][Data][Cr]

Data
0 : English
1 : France
2 : Deutch
3 : Spanish
4 : Italian
5 : Portugues
6 : Chinese
7 : Japanese
8 : Korean
9 : Russian

Acknowledgement

[i][][Set ID][][OK/NG][Data][x]

Transmission / Receiving Protocol

39. DPM Select (Command : f j)

▶ Set the DPM (Display Power Management) function.

Transmission

[f][j][][Set ID][][Data][Cr]

Data 0 : Off
1: On

Acknowledgement

[j][][Set ID][][OK/NG][Data][x]

40. Reset (Command : f k)

▶ Execute the Picture, Screen and Factory Reset functions.

Transmission

[f][k][][Set ID][][Data][Cr]

Data
0 : Picture Reset
1 : Screen Reset
2 : Factory Reset

Acknowledgement

[k][][Set ID][][OK/NG][Data][x]

Transmission / Receiving Protocol

41. S/W Version (Command : f z)

▶ Check the software version.

Transmission

[f][z][][Set ID][][Data][Cr]

Data FFH : Read

Acknowledgement

[z][][Set ID][][OK/NG][Data][x]

42. Input Select (Command : x b)

▶ To select input source for the Set.

Transmission

[x][b][ ][Set ID][ ][Data][Cr]

Data 20H : AV
40H : Component 1
41H : Component 2
60H : RGB (PC)
90H : HDMI/DVI (DTV)
A0H : HDMI/DVI (PC)

Acknowledgement

[b][ ][Set ID][ ][OK][Data][x]

Data 20H : AV
40H : Component 1
41H : Component 2
60H : RGB (PC)
90H : HDMI/DVI (DTV)
A0H : HDMI/DVI (PC)

IR Codes

How to connect

▶ Connect your wired remote control to Remote Control port on the Product.

Remote Control IR Code

▶ Output waveform

single pulse, modulated with 37.917KHz signal at 455KHz



Carrier frequency

FCAR = 1/Tc = fosc/12
Duty ratio = T1/Tc = 1/3

▶ Configuration of frame

• 1st frame


Lead code
Low custom code
High custom code
Data code
Data code
C0 C1 C2 C3 C4 C5 C6 C7 C0 C1 C2 C3 C4 C5 C6 C7 D0 D1 D2 D3 D4 D5 D6 D7 D0 D1 D2 D3 D4 D5 D6 D7

• Repeat frame



▶ Lead code



▶ Repeat code



▶ Bit description

• Bit "0"



• Bit "1"



▶ Frame interval : Tf

• The waveform is transmitted as long as a key is depressed.



IR Codes

Code(Hexa)	Function	Note
00	▲	R/C Button
01	▼	R/C Button
02	VOL(▶)	R/C Button
03	VOL(◀)	R/C Button
08	POWER ON/OFF	R/C Button (Power On/Off)
C4	POWER ON	Discrete IR Code(Only Power On)
C5	POWER OFF	Discrete IR Code(Only Power On)
09	MUTE	R/C Button
98	AV	R/C Button
0B	INPUT	R/C Button
0E	SLEEP	R/C Button
43	MENU	R/C Button
5B	EXIT	R/C Button
6E	PSM	R/C Button
44	SET	R/C Button
10	Number Key 0	R/C Button
11	Number Key 1	R/C Button
12	Number Key 2	R/C Button
13	Number Key 3	R/C Button
14	Number Key 4	R/C Button
15	Number Key 5	R/C Button
16	Number Key 6	R/C Button
17	Number Key 7	R/C Button
18	Number Key 8	R/C Button
19	Number Key 9	R/C Button
5A	AV	Discrete IR Code(Input AV Selection)
BF	COMPONENT1	Discrete IR Code(Input COMPONENT1 Selection)
D4	COMPONENT2	Discrete IR Code(Input COMPONENT2 Selection)
D5	RGB PC	Discrete IR Code(Input RGB PC Selection)
C6	HDMI/DVI	Discrete IR Code(Input HDMI/DVI Selection)
79	ARC	R/C Button
76	ARC (4:3)	Discrete IR Code(Only 4:3 mode)
77	ARC (16:9)	Discrete IR Code(Only 16:9 mode)
AF	ARC (ZOOM)	Discrete IR Code(Only ZOOM1, ZOOM2 mode)
99	AUTO CONFIC	Discrete IR Code

CHILD SAFETY:

It Makes A Difference How and Where You Use Your Flat Panel Display

Congratulations on your purchase! As you enjoy your new product, please keep these safety tips in mind:

THE ISSUE

- The home theater entertainment experience is a growing trend and larger flat panel displays are popular purchases. However, flat panel displays are not always supported on the proper stands or installed according to the manufacturer's recommendations.
- Flat panel displays that are inappropriately situated on dressers, bookcases, shelves, desks, speakers, chests or carts may fall over and cause injury.

THIS MANUFACTURER CARES!

- The consumer electronics industry is committed to making home entertainment enjoyable and safe.

TUNE INTO SAFETY

- One size does NOT fit all. Follow the manufacturer's recommendations for the safe installation and use of your flat panel display.
- Carefully read and understand all enclosed instructions for proper use of this product.
- Don't allow children to climb on or play with furniture and television sets.
- Don't place flat panel displays on furniture that can easily be used as steps, such as a chest of drawers.
- Remember that children can become excited while watching a program, especially on a "larger than life" flat panel display. Care should be taken to place or install the display where it cannot be pushed, pulled over, or knocked down.
- Care should be taken to route all cords and cables connected to the flat panel display so that they cannot be pulled or grabbed by curious children.

WALL MOUNTING: IF YOU DECIDE TO WALL MOUNT YOUR FLAT PANEL DISPLAY, ALWAYS:

- Use a mount that has been recommended by the display manufacturer and/or listed by an independent laboratory (such as UL, CSA, ETL).
- Follow all instructions supplied by the display and wall mount manufacturers.
- If you have any doubts about your ability to safely install your flat panel display, contact your retailer about professional installation.
- Make sure that the wall where you are mounting the display is appropriate. Some wall mounts are not designed to be mounted to walls with steel studs or old cinder block construction. If you are unsure, contact a professional installer.
- A minimum of two people are required for installation. Flat panel displays can be heavy.

CEA
Consumer Electronics Association

www.CE.org/safety

P/NO : 3840TRL098E (0801-REV00)